

# Calculation of a sandwich panel (1000 mm wide)

		Code					
Top facing	Material	1	steel				
	thickness in mm			0,50	SPESSORE LAMIERA		
Etf	E-modul in N/mm2			200 000			
	Max.Compr. in N/mm2			150			
Core	Material	4	Polistirene estruso				
	Thickness in mm			100,0	SPESSORE DEL PANNELLO		
Gc	G-modul in N/mm2			11,9			
	E-modul in N/mm2			20,0			
	Max. Shear strength in N/mm2			0,100			
Bottom facing	Material	1	steel				
	Thickness in mm			0,50	SPESSORE LAMIERA		
Ebf	E-modul in N/mm2			200 000			
	Max.Tension in N/mm2			150			
Span ( l )	in mm			7200	INSERIRE LUNGHEZZA PANNELLO		
Load	in kg/m2			25	INSERIRE CARICO KG/M2		
Max.defl./span ratio	1/ number			200	INSERIRE MAX FRECCIA AMMISSIBILE		
Max. Moment	in kNm			1,6			
Max. Shear	in kN			0,9			
HN=	in mm			50,50			
I moment of Inertia	in mm4			2525083			
Top facing stress	in N/mm2			32,24	Capacity =	21%	stress is OK
Bottom facing stress	in N/mm2			32,24	Capacity =	21%	stress is OK
Shear strength	in N/mm2			0,01	Capacity =	9%	stress is OK
Deflection		$d = \frac{5 * load * l^4}{384(Etf*Itf+Ebf*Ibf)} + \frac{load * l^2}{8 * hc * Gc}$					
d deflection	in mm			17,32	+	1,36	= 18,68 Deflection is OK
Maximum deflection	in mm						36,00
				Skin	Core		

Control of Buckling or Wrinkling of thin facings in compression.							
Max. allow. compr. stress		in N/mm2	0.5 ( Etf * Ec * Gc ) ^ 0.33	=	181,21	Wrinkling stress is OK	

Note:  
The information and data contained in this document are believed to be correct and are given in good faith. However they should be confirmed by a qualified engineer, in particular for thermal bow not taken in account for this computation. No liability, warranty or guarantee of final a sales specification and the sales Contract General Terms and product performance is created by this document.  
No freedom from any patent is granted or to be inferred. This document does not constitute Conditions continue to apply.